


Class I Microbiological Safety Cabinets





Welcome to Esco Lifesciences

Esco Lifesciences' vision is to provide enabling technologies for scientific discoveries to make human lives healthier and safer.

Esco Lifesciences is committed to delivering innovative solutions for the clinical, life sciences, research, industrial, laboratory, pharmaceutical, and IVF communities. With the most extensive product line in the industry, Esco has passed a number of international standards and certifications. Esco Lifesciences represents innovation and forward-thinking designs, that are of the highest standard quality since 1978.

Availability and Accessibility. Esco Lifesciences has headquarters in Singapore, Indonesia, and Philippines, with manufacturing facilities located in Asia and Europe. Research and Development (R&D) is conducted worldwide spanning the US, Europe and Asia. Sales, services, and marketing subsidiaries are located in 42 major markets including US, UK, Japan, China and India. Esco regional distribution centers are located in Singapore, Malaysia, Thailand, Vietnam, Myanmar, Indonesia, Philippines, Bangladesh, Hong Kong, Taiwan, South Korea, China, Japan, India, UAE, Central and South Africa, Denmark, Germany, Italy, Lithuania, Russia, United Kingdom, and USA. Because of our worldwide presence, you can be sure that Esco is within your reach.

High Quality, Reliable, and Dependable. Esco Lifesciences products are of high quality, reliable, and dependable. Crossfunctional teams from Esco Production, R&D, Quality Assurance, and Senior Management, are regularly assembled to review and implement areas for improvement.

Esco Lifesciences Cares for Your Safety. Esco Lifesciences focuses on providing safety not just for your samples, but also for you and the environment.

Esco Lifesciences Cares for Your Comfort. Building ergonomic designs and reducing noise levels of the units ensure comfort for our users.

Esco Lifesciences Cares for the Environment. Esco Lifesciences incorporates the latest proven technologically advanced components available. One in every four of Esco's employees is involved in Research and Development and are evaluating new components or designs for better efficiency. Whenever a new technology is available, Esco Lifesciences redesigns technology into our new products that will use lesser energy.

Customer Service and Support. Our service does not stop once purchase has been done. Esco Lifesciences gives on-time customer service such as service training, preventive maintenance, and re-certification, to respond to your equipment needs. Esco Lifesciences also offers free end-user seminars and provides educational materials and informative videos.

As Esco Lifesciences takes the opportunity to respond to the world's needs, we aim not only to contribute to the advancement of scientific discoveries but also in making the world a safer, healthier, and better place to live in.



Products and Applications

Sample Preparation

- Class I Biological Safety Cabinets
- Class II Biological Safety Cabinets
- Class II Type A2 Biological Safety Cabinets
- Class II Type B1 Biological Safety Cabinets
- Class II Type B2 Biological Safety Cabinets
- Class III Biological Safety Cabinets
- Horizontal Laminar Flow Cabinets
- Vertical Laminar Flow Cabinets
- Laboratory Animal Research Workstations
- Laboratory Centrifuges

Sample Cultivation

- CO₂ Incubators, Direct Heat Air-Jacketed
- CO2 Incubators with Cooling System
- CO₂ Incubators with High Heat Sterilization
- Laboratory Shakers

Life Sciences Laboratory Equipment

- **Amplification and Detection** • Conventional Thermal Cyclers
- Microplate Shakers
- PCR Cabinets

Sample Storage & Sample Protection Solutions

- Laboratory Refrigerators and Freezers
- Ultra-low Temperature Freezers
- Remote Monitoring, Datalogging, and Programming Software
- Wireless Monitoring System

Chemical Research

- Ducted Fume Hoods
- Ductless Fume Hoods
- Filtered Storage Cabinets
- Powder Weighing Balance Enclosure
- Exhaust Blowers
- Fume Hood Airflow Monitor

General Equipment

Laboratory Thermostatic Products

- Forced Convection Laboratory Oven
- Forced Convection Laboratory Incubator
- Natural Convection Laboratory Incubator
- Refrigerated Laboratory Incubator

Medical / IVF Equipment

Sample Handling

- Esco Multi-Zone ART Workstation
- AVT Anti-Vibration Table
- Versati™ Tabletop Centrifuge Refrigerated

Embryo Culture

- MIRI® Multiroom Incubator
- MIRI® II-12 Multiroom Incubator
- Mini MIRI® Humidity Incubator
- Mini MIRI® Dry Incubator
- CelCulture® CO₂ Incubator

Innovative Time-Lapse Imaging

MIRI[®] Time-lapse Incubator

Accurate Quality Control

• MIRI® GA Gas and Temperature Validation Unit

Unique Consumables

CultureCoin®

Healthcare

Esco Pharma Products

Airflow Containment

- BioBooth®
- Ceiling Laminar Airflow (CLAF)
- Cytoculture® Cytotoxic Safety Cabinet (CYT)
- Pharmacon™ Downflow Booth
- Esco Garment Storage Cabinet
- Esco Glassware Hoods
- Laminar Flow Horizontal/Vertical Trolley (LFH/VT)
- Laminar Flow Straddle Units
- Evidence Drying Cabinet

Isolation Containment

- Advanced Processing Platform Isolator (APPI)
- Aseptic Containment Isolator (ACTI)
- Blood Cell Labelling Isolator
- Streamline® Closed Restricted Access Barrier System (SLC-RABS)
- Containment Barrier Isolator (CBI)
- CBI-Unidirectional (CBI-U)
- CBI-Turbulent (CBI-T)
- CBI-Class III Biosafety Cabinet (CBI-III)
- CBI-Hybrid (CBI-H)
- Isoclean® Healthcare Platform Isolator (HPI) - HPI-G3-Without Filter Below Work Zone
- HPI-G3-With Filter Below Work Zone
- HPI-Inflatable Seal (HPI-IS)
- HPI Inflatable Seal BioVapTM (HPI-IS-BVP)
- General Processing Platform Isolator (GPPI)
- GPPI-Inflatable Seal (GPPI-IS)
- GPPI-Static Seal (GPPI-SS)
- Streamline® Compounding Isolator (SCI)
- Streamline® Containment Isolator Class III (SCI-III)
- Technetium Dispensing Isolator
- Turbulent Flow Aseptic Isolator™ (TFAI™)
- Weighing and Dispensing Containment Isolator (WDCI)

Cross Contamination Facility Integrated Barrier

- BioPass™ Pass Through
- · Cleanroom Air Showers
- Dynamic Pass Boxes/ Dynamic Floor Laminar Hatches
- Infinity® Air Shower Pass Box
- Esco Sputum Booth
- Infinity® Pass Boxes Infinity® Cleanroom Transfer Hatch
- Soft Capsule® Soft Wall Cleanroom

Ventilation Containment

• Ventilated Balance Enclosure

Esco VacciXcell Products

Tide Motion Bioreactors

- CelXrocker™ (CXR)
- MiniTide®
- CelCradle™ (CC) • CelCradle X® (CCX)
- TideXcell® (TXL)

Stirred Tank Bioreactors

- BioXcell®
- StirCradle™
- StirCradle™ PRO
- VXL™ Hybrid

Harvesting System

- CelShaker™
- CelCradle X® Semi-automated Harvester System(CCX-SAH)
- TideXcell® Harvester System (TXLHS)

Cell Culture Monitoring, Media and Consumables

- Super Plus™
- Plus™ Vero
- PlusTM MDCK • Plus™ MDCK II
- BioNOC™ II macrocarriers
- GlucCell™ Glucose Monitoring System
- CVD Kit

Filling Line Equipment

- Traditional Filling Line
- cRABS (Closed Restricted Access Barrier System)
- oRABS (Open Restricted Access Barrier System)

Integrated Solutions

- Cell Processing Isolator (CPI)
- Cell Processing Center

Esco TaPestle Rx Products and Services Pharmacy Automation and Compounding Supply

- Compounding Pharmacy Isolators (SCI, HPI, CBI, GPPI)
- Safety Cabinets and Enclosures (CYT, Class II BSC, VBE,
- Aseptic Filling Systems

Radiopharmacy Equipment

- Blood Cell Labeling Isolator
- Cytoculture® Lead-Shielded Class II Biosafety Cabinet

• GMP-compliant Radioisotope Dispensing Isolator


• Radiopharmacy Hood (Lead Shielded Biological Safety

- Frontier® Radioisotope™ Fume Hood
- Cabinet) · Technetium Dispensing Isolator



RS 232 Port and Zero Volt Relay Contact

- RS 232 Port to send operational information to Building Management System (BMS)
- Zero Volt Relay Contact to turn ON/OFF exhaust blower and signal the building alarm



ESCO.

Optional Secondary H14 or Carbon Filter H14 Filter

■ 10x filtration efficiency of HEPA filter





Sentinel™ Gold Microprocessor Controller

- Displays all safety information on one screen
- Centered and angled down for easy reach & viewing



Hinged Window

- 90° opening for an easy workzone access
- 8 mm UV Resistant Polycarbonate Window
- Gasket-surrounded window to provide airtight seal for better safety.



Easy to Clean Back Wall

- Large back wall radius for easy cleaning
- With UV Lamp Provision



UV Door

- Safety door against UV light
- Provides air-tight seal during decontamination
- Integrated with VHP Injection Port for easy connection to VHP/HPV generator



Esco Class I Microbiological Safety Cabinets has been certified by PHE / Public Health England (formerly HPA) for compliance to EN 12469




Airflow Sensor

0000

- Monitors real-time airflow for safety
- Alert the user if airflow is insufficient

Energy Efficient DC ECM Motor

- 70% Energy savings from AC motor
- Stable airflow, despite building voltage fluctuations
- Standby Mode to further reduce power consumption by 60%



Airstream,

Conventional AC motor motor voltage fluctuation airflow fluctuation Esco DC ECM motor stable motor voltage stable airflow


Work Top

- 1.2 mm (0.05") 18 gauge SS 304, 4B Finish
- Spill-retaining work top design with a recessed central area contains accidental liquid spills.



Isocide™ Powder Coat

- Silver-ion impregnated powder coat
- Inhibit microbial growth to improve safety



Available in 1.2 meter / 4 ft width

	Biological Safety Cabinets	Filtration	Electrical Safety
Standards Compliance	EN 12469, Europe SANS12469, South Africa	EN-1822 (H14), Europe IEST-RP-CC001.3, USA IEST-RP-CC007, USA IEST-RP-CC034.1, USA	IEC61010-1, Worldwide EN-61010-1, Europe



TECHNICAL SPECIFICATIONS						
Model		AC1-3E8	AC1-4E8			
External Dimensions (W x D x H)		1035 mm x 731 mm x 1395 mm (40.7" x 28.8" x 55")	1340 x 731 x 1395 mm (52.7" x 28.8" x 55")			
Gross Internal Dimensions (W x D x H)		918 mm x 668 mm x 670 mm (36.1" x 26.3" x 26.4")	1220 x 668 x 670 mm (48" x 26.3" x 26.4")			
Usable Work Area		0.57 m2 (6.1 sq.ft)	0.76 m2 (8.2 sq.ft)			
Maximum Window Opening (at 90° opening)		556 mm (21.9")	556 mm (21.9")			
Working Opening/ Tested Opening		200 mm (7.9")	200 mm (7.9")			
Average Inflow Velocity		0.85 m/s (167 fpm)	0.85 m/s (167 fpm)			
Airflow Volume	Inflow	526 m³/h (310 cfm)	758 m³/h (446 cfm)			
	Exhaust	526 m³/h (310 cfm)	758 m³/h (446 cfm)			
	Required Exhaust with Optional Thimble Exhaust Collar	1219 m³/h (717 cfm)				
	Static Pressure for Optional Thimble Exhaust Collar	85 Pa (0.34 in H₂O)				
HEPA Filter Typical Efficiency		>99.999% at 0.1 to 0.3 micron, ULPA as per IEST-RP-CC001.3 USA >99.999% at MPPS, H14 as per EN 1822 EU				
Sound Emission in Typical Lab Room per EN 12469		60.8 dBA	48.4 dBA			
LED Lamp Intensity (lux)		>1200 lux (>111 foot candles)				
	Main body	1.2 mm (0.08") /18 gauge EG Steel with Isocide™ Oven-Baked Epoxy-Polyester Powder Coating				
Cabinet Construction	Work Zone	Tray: 1.2 mm (0.08")/18 gauge, SS 304, 4B Finish	Table: 1.2 mm (0.08") / 18 gauge, SS 304, 4B Finish			
	Side Walls	5 mm(0.2") UV Absorbing Tempered Glass	5 mm (0.2 ") UV Absorbing Tempered Glass			
Electrical	Cabinet Full Load Amps (FLA)	8.2	8.1			
	Heat Load (BTU / Hr)	460	628			
Nominal Power Consumption		235 W	184 W			
Net Weight *		225 kg	230 Kg (507 lbs)			
Shipping Weight *		251 kg	285 Kg (628 lbs)			
Shipping Dimensions, Maximum (W x D x H)*		1120 mm x 850 mm x 1950 mm (44.1" x 33.5" x 76.8")	1450 x 820 x 1760 mm (57.1" x 32.3" x 69.3")			
Shipping Volume, Maximum *		1.86 m³	2.09 m³			


^{*} Cabinet only, excludes optional stand.




Accesories for AC1 Biological Safety Cabinets					
		AC1-3E8	AC1-4E8		
Cabinet	Stainless Steel Side Wall		AC1-4E8 2010732		
Optional Secondary Filter	Secondary H14 Filter	HP-AC1-3 5080228	HP-AC1-4 5080138		
	Secondary Carbon Filter	CRF/SEC-AC1-3 5080226	CRF/SEC-AC1-4 5080139		
Exhaust Ducting	Exhaust Hard Ducting (with VHP out Port)	EHD AC1-3 5172154	EHD AC1-4 5170666		
	Anti-blowback Valve 10"	ABBV-10P 5170352			
	Tri-safe Exhaust Collar with Alarm	TEM-4 2010606			
	Exhaust Damper	B2-DAMPER 5170352			
Hydrogen Peroxide Decontamination Kit	UV Door (with VHP In Port)	UV DOOR AC1-3 5072158	UV DOOR AC1-4 5090044		
	VHP Out Top Box for Cabinet WITHOUT Exhaust Collar Installed (Ø 1")	VHP OUT TOP BOX 4ft 5172156	VHP OUT TOP BOX 4ft 5170665		
Work Zone	UV Lamp	UV-15A 5170251	UV-15A 5170255		
	IV Bar	IV-910 5170499	IV-910 5170231		
	Pre-filter	5090093	5090045		
Electrical Outlet	Universal	EO-UNI 5170060			
Service Fixtures	EU SF-Gas-20 mm	SF-1G20 5170410			
	EU SF-Vacuum-20 mm	SF-1V20 5170457			
	EU SF-Air-20 mm	SF-1A20 5170502			
	EU SF-Nitrogen-20 mm	SF-1N20 5170503			
	EU SF-Water-20 mm	SF-1W20 5170458			
	EU SF-Universal-22 mm	SF-2U22 5170504			
	Fixed Stand with Leveling Feet, 28" height	SAL-3A0 Gen 2 5130170	SAL-4A0 Gen 2 5130134		
	Fixed Stand with Leveling Feet, 34" height	SAL-3B0 Gen 2 5130174	SAL-4B0 Gen 2 5130175		
Support Stands, Ships Flat	Fixed Stand with Caster Wheels, 28" height	SPC-3A0 Gen 2 5130013	SPC-4A0 Gen 2 5130152		
	Fixed Stand with Caster Wheels, 34" height	SPC-3B0 Gen 2 5130018	SPC-4B0 Gen 2 5130166		
	Motorized Height Stand with Caster Wheels	SPM-3A_	SPM-4A_		
Misc	IQ OQ Protocol	9010179			




AC1 Biological Safety Cabinet Engineering Drawing



- 1. Exhaust Ducting (optional)
- 2. Electrical Panel
- 3. Diffuser / Optional Pre-filter
- 4. LED Lamp
- 5. Side Tempered Glass
- 6. Stainless Steel Table
- 7. Optional Secondary H14 Filter / Carbon filter)
- 8. DC FCM Blower
- 9. Inflow Sensor
- 10. Main H14 Filter
- 11. IV Bar Retrofit Kit Provision
- 12. UV Lamp Provision





- 13. Standard Electrical Outlet Kit Provision
- 14. Service Fixtures Kit Provision (2 on each side)
- 15. 2 Sets Zero Volt Relay Contact
- 16. RS 232 Port
- 17. Power Inlet

- 18. Sentinel™ Gold Microprocessor System
- 19. Hinged Front Door
- 20. 8 mm UV Resistant Polycarbonate Window
- 21. Air Tight UV / Decontamination Panel

Follow us on social media, download our apps, and scan the QR code for more info.























Esco Micro Pte. Ltd. • 19 Changi South Street 1 • Singapore 486779 Tel +65 6542 0833 • mail@escolifesciences.com www.escolifesciences.com

Esco Technologies, Inc. • 903 Sheehy Drive, Suite F, Horsham, PA 19044, USA Tel: +1 215-441-9661 • Fax 484-698-7757 eti.admin@escolifesciences.com

Esco Lifesciences Group Offices: Bangladesh | China | Denmark | Germany | Hong Kong | India | Indonesia | Italy | Japan | Lithuania | Malaysia | Myanmar | Philippines | Russia | Singapore | South Africa | South Korea | Taiwan | Thailand | UAE | UK | USA | Vietnam

